

RV 80

Somerset Stone and Stove LLC
 PO Box 12
 1078 Kennedy Memorial Drive
 Oakland, ME 04963
 (207) 465-9800
 www.somersetstoneandstove.com



AIR		
HEAT INPUT	BTU/hr	10,000 - 40,000
HEAT OUTPUT	BTU/hr	8,500 - 35,000
FEED RATE	lb/hr	1.5 - 4.41
EFFICIENCY (based on LHV)	%	87
VENTING SIZE	Ø mm	80/3.15
HOPPER CAPACITY	lb	35
BURN TIME	hr	7.5 - 22
NET WEIGHT	lb	270
EPA Emission Rate	gr/h	0.6



RAVELLI DYNAMIC SYSTEM

RDS is Ravelli's innovative system for automatically regulating combustion parameters and ensuring maximum efficiency and safety from your stove.



FIREX 600

All Ravelli's products have a combustion chamber made from FIREX 600, a vermiculite based material developed by Gruppo Ravelli after long and extensive research.



STAINLESS STEEL HEAT EXCHANGER

A stainless steel heat exchanger means increased fire resistance and reduced wear



CAST IRON FIRE POT

Ravelli professionally engineered firepot is extremely heavy duty, It can handle the constant heating of a pellet fire and his very high temperature.



REMOTE CONTROL

A practical and convenient remote control allows you to adjust temperature and power as required. Moreover, it helps to perform the stove programming laying comfortably on the sofa.



ASH PAN

A functional and easily accessible ash pan collects all the burned out ash.

