

RV 100 CLASSIC

AIR		
HEAT INPUT	BTU/hr	10,000 - 50,000
HEAT OUTPUT	BTU/hr	8,500 - 44,000
FEED RATE	lb/hr	1.32 - 5.29
EFFICIENCY (based on LHV)	%	87
VENTING SIZE	Ø mm	80/3.15
HOPPER CAPACITY	lb	55
BURN TIME	hr	10.4 - 41.7
NET WEIGHT	lb	330
EPA Emission Rate	gr/h	2,9



RAVELLI DYNAMIC SYSTEM

RDS is Ravelli's innovative system for automatically regulating combustion parameters and ensuring maximum efficiency and safety from your stove.



FIREX 600

All Ravelli's products have a combustion chamber made from FIREX 600, a vermiculite based material developed by Gruppo Ravelli after long and extensive research.



STAINLESS STEEL HEAT EXCHANGER

A stainless steel heat exchanger means increased fire resistance and reduced wear



CAST IRON FIRE POT

Ravelli professionally engineered firepot is extremely heavy duty, It can handle the constant heating of a pellet fire and his very high temperature.



REMOTE CONTROL

A practical and convenient remote control allows you to adjust temperature and power as required. Moreover, it helps to perform the stove programming laying confortably on the sofa.



ASH PAN

A functional and easily accessible ash pan collects all the burned out ash.

